



504-393-1701

800-925-4966

KUBOTA POWER UNIT SPECIFICATIONS

Model:	D1703ME3BHYDASR
HP Rating:	34.98 HP @ 2800 RPM
Radiator:	Mounted radiator, coolant recovery tank
Air Cleaner:	Mounted dry air cleaner, stainless steel manual air intake shutdown, 6ft pull cable,
Muffler:	Mounted muffler, spark arrestor
Fuel Filter:	Mounted spin on fuel filter assy
Mount Feet:	Structural steel mounting feet
Flywheel Power Take Off:	Hydraulic pump adaptor SAE 2 B 7/8" 13T spline
Engine Controls:	Mechanical engine controls, Sentinel hi temp and low oil shutdown, air start, idler pulley assy, 6ft mico speed contril cable, 6ft engine shutdown cable, stainless steel pivot pin linkage and cable hold down brackets
Accessories:	EZ oil drain valve, 2 part epoxy coating, USCG approved JIC fuel fittings, flame resistant fuel and oil hoses JIC fitted, deluxe gauge panel with oil temp gauge, water temp gauge, vibration hour meter
Summary:	This engine is assembled for hydraulic pump application. It meets Class 1 Div 2 requirments. The engine is air start with spark arrestor, manual air intake shutdown, USCG approved fuel and oil hose and connections and epoxy coated.