



**OFFSHORE READY
HYDRAULIC POWER UNIT
MAX RATINGS 14 GPM @ 2000 PSI**

SPECIFICATIONS:

MODEL: HPU1420SM40

ENGINE: Kubota D1005 liquid cooled diesel engine rated 24 hp @ 3000 rpm, assembled with mounted radiator, coolant recovery tank, air cleaner, manual air intake shutdown, muffler, spark arrestor, fuel filter, air starter, 8 gallon aluminum fuel tank, oil pressure gauge, hour meter

HYDRAULICS: Gear drive pump rated up to 3500 rpm @ 2500 psi, import SAE 16, out port SAE 12, 40 gallon reservoir, oil site/temp glass, temperature gauge, 50 micron suction strainer, flow control, adjustable relief valve, inline flow meter, return filter, SS 3000 pressure gauge, 3/4" quick disconnects

SKID: Structural steel all welded and galvanized roll frame, engine vibration plate with stableflex vibration isolators, drip pan, bottom drain, 4 corner lift, forklift pockets

DIMENSIONS/WEIGHT: L 60" x W 32" x H 40" / 1500 lbs.

WARRANTY: 2 year engine warranty major components, 1 year all other engine components, 1 year hydraulic pump warranty, 90 day all accessories

SUMMARY: This hydraulic power unit is offshore ready. It meets Class I Div 2 requirements. It is designed in form and function to provide portable power for hydraulic power tools, hydraulic ram and any other hydraulic equipment. The unit is assembled to meet the harsh offshore environment. The skid design insures protection to all components and allows for safe transportation

SpecHPU1420SM40