



Phone 800-925-4966

Fax 504-393-1627

OFFSHORE READY HYDRAULIC POWER UNIT 20 GPM @ 2200 PSI

SPECIFICATIONS:

MODEL: HPU2022SM60

ENGINE: Kubota D1703M liquid cooled 3 cylinder diesel engine, rated 36 hp @ 2800 rpm, assembled with mounted radiator, coolant recovery tank, air cleaner, manual air intake shutdown, muffler, spark arrestor, fuel filter, air starter, idler pulley assy, hydraulic pump adaptor, 18 gallon Coast Guard approved fuel tank with fuel gauge and bottom shutoff valve

HYDRAULICS: Parker Commercial Hydraulic gear drive pump rated up to 2800 rpm @ 2500 psi, import SAE 16, our port SAE 12, 60 gallon reservoir, oil site/temp glass, temperature gauge, 50 micron suction strainer, adjustable flow control, relief valve, inline flow meter, return filter, SS 5000 psi pressure gauge, 3/4" quick disconnects, 3/4" piping

SKID: Structural steel all welded galvanized roll frame, engine vibration plate with stableflex isolators, deluxe steel expanded metal radiator guard, beveled drip pan, bottom drain, 4 corner lift, forklift pockets 4"x10"

DIMENSIONS/WEIGHT: L 66" x W 34" x H 50" / 2500 lbs.

WARRANTY: 2 year engine warranty major components, 1 year all other engine components, 1 year hydraulic pump warranty, 90 day all accessories

SUMMARY: This hydraulic power unit is offshore ready. It meets Class I Div 2 requirements. It is designed in form and function to provide portable power for hydraulic power tools, hydraulic rams and other hydraulic equipment. The unit is assembled to meet the harsh offshore environment. All hardware is stainless steel. The skid design insures protection to all components and allows for lifting and safe transportation.

SpecHPU2022SM60