



**OFFSHORE READY
HYDRAULIC POWER UNIT
45 GPM @ 3000 PSI**

SPECIFICATIONS:

MODEL: HPU4530SM80

ENGINE: Kubota V3800DIT liquid cooled 4 cylinder turbo charged diesel engine rated 95 hp @ 2600 rpm net intermittent , assembled with mounted radiator, coolant recovery tank, air cleaner, manual air intake shutdown, muffler, spark arrestor, fuel filter, 30 gallon fuel tank, weatherproof engine controls, hi temp and low oil shutdown, 12 volt battery with box and cables

HYDRAULICS: Gear drive pump rated up to 2600 rpm @ 3000 psi, in port SAE 16, out port SAE 12, 80 gallon reservoir, oil site/temp glass, temperature gauge, 50 micron suction strainer, flow control, adjustable relief valve, inline flow meter, return filter, SS pressure gauge, 3/4" quick disconnects

SKID: Structural steel all welded galvanized roll frame, engine vibration plate with stableflex vibration isolators, drip pan with bottom drain, center point lift, forklift pockets

DIMENSIONS/WEIGHT: Approximate L 74" x W 40" x H 55"

WARRANTY: 2 year engine warranty major components, 1 year all other engine components, 1 year hydraulic pump warranty, 90 day all accessories

SUMMARY: This hydraulic power unit is offshore ready. It is designed in form and function to provide portable power for hydraulic power tools, hydraulic ram and other hydraulic equipment. The unit is assembled to meet the harsh offshore environment. The skid design ensures protection to all components and allows for safe transportation.

(SpecHPU4530SM80)