



Phone 800-925-4966

Fax 504-393-1627

KUBOTA / AMT 3X3 DIESEL TRASH PUMP OFFSHORE READY

SPECIFICATIONS:

MODEL: DPS3X3TAMT

ENGINE: Kubota OC60 air/oil cooled single cylinder diesel engine rated 6.0 hp @ 3600 rpm, 12 volt electric start, recoil start back up, sealed and mounted wiring harness with key switch, manual air intake shutdown, spark arrestor, fuel tank, 12 volt battery, box and cables

PUMP: 3X3 AMT trash pump, sand cast aluminum housing, cast iron volute and impeller, silicone carbide mechanical seal, buna o-rings and check valve, maximum flow 300 gpm, 25 ft. vertical suction lift, $\frac{3}{4}$ solids handling, EZ impeller clean out, suction and discharge cam locks

SKID: Structural steel all welded and galvanized roll frame with drip pan, 4 Corner lift eyes, vibration isolators

DIMENSIONS: L 33" x W 28" x H 24" / 285 lbs.

OPTIONS: Recoil start only, wheel kit with 12" pneumatic tires

SUMMARY: The Kubota engine and AMT pump are matched to provide high flow and solids handling capability. This pump is designed for the rental industry to meet heavy duty industrial commercial pump applications. The pump set meets standard offshore requirements and can be used in hazardous locations

(SpecDPS3X3TAMT)