



OFFSHORE READY DIESEL COMPRESSOR PACKAGE 36 ACFM @ 175 PSI

SPECIFICATIONS:

MODEL: DQC350SM30

ENGINE: Kubota ZH602 liquid cooled 2 cylinder diesel engine, rated 16 hp @ 3600 rpm, assembled with mounted radiator, coolant recovery tank, air cleaner, manual air intake shutdown, muffler, spark arrestor, weatherproof engine controls, Murphy hi temp and low oil shutdown

COMPRESSOR: Quincy 350 air compressor rated 36 ACFM @ 175 PSI @ 940 RPM, 2 stage, pressure lubricated, spin on oil filter, dry type air filter, 2 groove power ban belt drive, unloader valve, load genie, pressure gauge

SKID: All welded galvanized roll frame with vibration plate, stableflex isolators, beveled drip pan, bottom drain, 4 corner lift eyes, structural steel belt guard with expanded metal for ventilation, 30 gallon ASME approved volume tank, 12 volt battery with box and cables, 12 gallon aluminum CG approved fuel tank with gauge, stainless steel hardware

WEIGHT / DIMENSIONS: L 78" x W 46" x H 49" / 1800 lbs.

WARRANTY: 2 year engine warranty major components, 1 year all other engine components, 1 year compressor warranty, 90 days all accessories

SUMMARY: This engine/compressor package is offshore ready. It is designed in form and function for various applications including cold starting, operating air tools, supplying rig air and any other application where portable compressed air is needed. The unit is assembled to meet the harsh offshore environment. The skid design ensures protection to all components and allow for safe transportation.

SpecDQC350SM30