



Phone 800-925-4966

Fax 504-393-1627

EXPLOSION PROOF PRESSURE WASHER

MODEL: EXP3004D

RATED: 4 gpm @ 3000 psi

MOTOR: Marathon 10 hp, 1800 rpm, 3 phase, 460 volt, Explosion Proof

PUMP: Triples Pump Direct Drive, rated 4 gpm @ 3000 psi

CONTROLS: Furnas XTL Starter Explosion Proof w/Start-Stop push buttons, 25ft Whip extension cord XP.

COUPLING: Omega Elastomer Flex Coupling

SKID: Structural Steel, Galvanized, 4Corner Lift Eyes, Forklift Pockets, Hose Rack

ACCESSORIES: Stainless Steel Float Tank, Inlet mesh filter, Trap pressure Adjustable unloader, Thermo Pump Protector, Heavy Duty flex coupling and guard, 50 ft discharge hose, chemical injector, 5 spray nozzles, 36" lance and shutoff gun

Summary: This unit features a direct drive pump. The critical component in this application is the heavyduty flex coupling. Proper alignment and the balanced coupling will reduce vibration and extend the life of the coupling insert. The explosion proof furnas controls allow for easy, safe and trouble free operation. The large capacity (7gallon) stainless steel float tank provides a dual water feed into the pump to insure adequate water supply in low pressure (tank feed) applications. Bypass water is returned back to the float tank to keep water cool for extended run time in bypass mode. All accessories meet or exceed manufactures specifications.

(SpecEXP3004D)