



## **EXPLOSION PROOF PRESSURE WASHER**

**MODEL:** EXP7005D

**RATED:** 5 gpm @ 7000 psi

**MOTOR:** Marathon 25 hp, 1800 rpm, 3 phase, 460 volt, Explosion Proof

**PUMP:** Triples Pump Direct Drive, rated 5 gpm @ 7000 psi

**CONTROLS:** Furnas XTL Starter Explosion Proof w/Start-Stop push buttons, 25ft Whip extension cord XP.

**COUPLING:** Omega Elastomer Flex Coupling

**SKID:** Structural Steel, Galvanized, 4Corner Lift Eyes, Forklift Pockets, Hose Rack

**ACCESSORIES:** Stainless Steel Float Tank, Inlet mesh filter, Trap pressure Adjustable unloader, Thermo Pump Protector, Heavy Duty flex coupling and guard, 50 ft discharge hose, chemical injector, 5 spray nozzles, 36" lance and shutoff gun

**Summary:** This unit features a direct drive pump. The critical component in this application is the heavyduty flex coupling. Proper alignment and the balanced coupling will reduce vibration and extend the life of the coupling insert. The explosion proof furnas controls allow for easy, safe and trouble free operation. The large capacity (7gallon) stainless steel float tank provides a dual water feed into the pump to insure adequate water supply in low pressure (tank feed) applications. Bypass water is returned back to the float tank to keep water cool for extended run time in bypass mode. All accessories meet or exceed manufactures specifications.

(SpecEXP7005D)