



Phone 800-925-4966

Fax 504-393-1627

OFFSHORE READY HDRAULIC POWER UNIT 08-10 GPM @ 1500 PSI

SPECIFICATIONS:

MODEL: HPU0810

ENGINE: Kubota OC95 single cylinder air/oil cooled diesel engine rated 9.5 hp @ 3600 rpm, assembled with 12 volt electric start, recoil hand start, air cleaner, air intake shutdown, muffler, spark arrestor, fuel filter, 8 gallon aluminum fuel tank

HYDRAULICS: Gear drive pump rated up to 3600 rpm @ 2500 psi, in port SAE 12, out port SAE 10, 17 gallon reservoir, oil site/temp glass, 50 micron suction strainer, flow control with adjustable, relief valve, inline flow meter, return filter, SS 3000 pressure gauge, 3/4" quick disconnects

SKID: Aluminum all welded wheel kit handles, heavy duty casters, engine vibration plate with vibration isolators, drip pan, bottom drain, center point lift, SS hardware, 12 volt battery with box and cables

DIMENSIONS/WEIGHT: L 49" x W 29" x H 39" / 500 lbs.

WARRANTY: 2 year engine warranty major components, 1 year all other engine components, 1 year hydraulic pump warranty, 90 day all accessories

SUMMARY: This portable hydraulic power unit is offshore ready. It is designed in form and function to provide hydraulic power for power tools, motors and a variety of equipment. The unit is assembled to meet the harsh offshore environment. The aluminum skid design protects all components and allows for safe transportation.

SpecHPU0810