



**OFFSHORE READY  
HYDRAULIC POWER UNIT  
20 GPM @ 3000 PSI**

**SPECIFICATIONS:**

**MODEL:** HPU2030SM60

**ENGINE:** Kubota V2203M (tier 3 certified) liquid cooled 4 cylinder diesel engine rated 56 hp @ 2800 rpm with mounted radiator, coolant recovery tank, air cleaner, manual air intake shutdown, muffler, spark arrestor, fuel filter, 12 volt electric start, battery, box and cables (air starter optional), F.W. Murphy mechanical hi temp and low oil shutdown weatherproof engine control panel

**HYDRAULICS:** Commercial hydraulic gear drive pump rated up 2800 rpm @ 3000 psi, omni directional dual flow control valve, 60 gallon reservoir, large capacity clean out ports, oil site/temp glass gauge, 50 micron suction strainer, return filter, pressure gauge

**SKID:** Structural steel all welded roll frame, engine vibration plate with stableflex isolators, deluxe steel expanded metal radiator guard, beveled drip pan, bottom drain, 4 corner lift, forklift pockets (4"x10") 18 gallon aluminum fuel tank with fuel gauge, CG approved

**OPTIONS:** Air starter, Sentinel mechanical engine shutdown system, full aluminum enclosure, half enclosure

**DIMENSIONS/WEIGHT:** L 78" x W 41" x H 55" / 3000 lbs.

**WARRANTY:** 2 year engine warranty major components, year all other engine components, 1 year hydraulic pump warranty, 90 day all accessories

**SUMMARY:** This hydraulic power unit is offshore ready. It is designed to provide portable power for hydraulic winches, power tools, hydraulic rams and any other hydraulic powered equipment. The unit is assembled to meet offshore standards for lifting, hazardous location and environments concerns. The skid design provides protection to all components and allows for safe lifting and transportation.

(SpecHPU2030)