



**OFFSHORE READY
HYDRAULIC POWER UNIT
MAX RATINGS 25 GPM @ 1500 PSI**

SPECIFICATIONS:

MODEL: HPU2515SM100PCPOC

ENGINE: Kubota D1703M liquid cooled diesel engine rated 37 hp @ 2800 rpm, assembled with mounted radiator, coolant recovery tank, air cleaner, poly manual air intake shutdown, muffler, spark arrestor, fuel filter, electric starter, mounted battery box with battery and cables, 12 gallon aluminum fuel tank, F.W. Murphy Engine controls (Low Oil/High Temp Shutdown, hour meter, key switch, 4 ft. loomed wire harness) in a non-metallic, weather proof enclosure.

HYDRAULICS: Pressure compensated pump rated up to 2800 rpm @ 4500 psi, in port SAE #20, out port SAE #16, 100 gallon reservoir, environmentally friendly hydraulic oil, oil site/temp glass, temperature gauge, 50 micron suction strainer, flow control, adjustable relief valve, inline flow meter, return filter, SS 3000 pressure gauge, 3/4" quick disconnects, hydraulic oil cooler.

SKID: Structural steel all welded and galvanized roll frame, engine vibration plate with stableflex vibration isolators, drip pan, bottom drain, 4 corner lift and forklift pockets.

DIMENSIONS/WEIGHT: L 82" x W 42" x H 60" / 2250 lbs.

WARRANTY: 2 year engine warranty major components, 1 year all other engine components, 1 year hydraulic pump warranty, 90 day all accessories.

SUMMARY: This hydraulic power unit is intended for harsh industrial use. It is designed in form and function to provide portable power for hydraulic power tools, hydraulic ram and any other hydraulic equipment. The unit is assembled to meet the harsh industrial environment. The skid design insures protection to all components and allows for safe transportation.

SpecHPU2515SM100PCPOC

12/16/13