



SUBSURFACE PRESSURE WASHING SYSTEM

LIST OF SPECIFICATIONS:

MODEL No. CT1620BAS rated 16 GPM @ 2000 psi

ENGINE: Kubota D1105E rated 26 hp @ 3000 rpm, mounted radiator, coolant recovery tank, air cleaner, auto/manual air intake shutdown, 6ft. pull cable, muffler, spark arrestor, fuel filter, air starter w/lubricator, push button pilot valve, idler pulley assy (NO ELECTRICS), speed control cable, engine shutdown cable, EZ oil drain valve, epoxy coated (customer supplies paint)

PUMP: Triplex pump, stainless steel fluid end, belt drive, 2 groove power ban, inlet water filter, Ingersoll Rand air operated charge pump (optional stainless steel centrifugal charge pump), all components epoxy coated (customer supplies paint)

TRIGGER GUN / ACCESSORIES: Subsurface rated trigger dump gun, stainless steel barrel nozzle, stainless steel diffuser, 100ft. high pressure discharge hose (Optional Hose Reel), stainless steel QD's

SKID: Structural steel all welded and galvanized skid (SHELL COMPLIANT), box tubing base, forklift pockets, full containment drip pan, bottom drain, deluxe vibration isolation plate with stableflex neoprene isolators, roll frame, 4 corner lift, 12 gallon aluminum USCG approved fuel tank, deluxe control panel with water temp gauge, oil pressure gauge, vibration hour meter, removable aluminum hood, removable radiator guard, stainless steel hardware

DIMENSIONS / WEIGHT: Approx: L 50" x W 30" x H 54" , 1600 lbs.

WARRANTY: Engine warranty is for 2 years major components, 1 year on all other components, 90 days on accessories, Pump warranty is for 1 year and 90 days on all accessories. Warranty does not cover environmental damage or lack of maintenance. All warranty is provided by Gulf Engine. Warranty covers land transportation only.

SUMMARY: This underwater pressure washer is designed, fabricated and assembled to meet sever duty offshore applications. It complies with current SHELL / USCG regulation

SPECIFICATIONS AND PRICING SUBJECT TO CHANGE WITHOUT NOTICE

(SpecCT1620BAS)