



Phone 800-925-4966

Fax 504-393-1627

**KUBOTA / AMT
2X2 DIESEL TRASH PUMP
RENTAL DUTY**

SPECIFICATIONS:

MODEL: DPH2X2TAMT

ENGINE: Kubota OC60 (tier 3 certified) 6.0hp air/oil cooled diesel engine, electric start with recoil start back up, mounted key switch and wiring harness, 12 volt battery with box and cables

PUMP: AMT 2X2 trash pump, cast aluminum housing, cast iron volute, impeller and wear plate, silicone carbide mechanical seal, Buna o-rings and check valve, maximum flow 180 gpm, 25 ft. vertical suction lift, 3/4" solids handling, EZ impeller clean out, suction and discharge camlocks

SKID: Structural steel all welded and galvanized roll frame (lifetime warranty), center point lift eye, vibration isolators

WARRANTY: 2 year engine (major components) 1 year all other, 1 year pump

DIMENSIONS: L 33" x W 28" x H 24" / 185 lbs.

OPTIONS: Spark arrestor, manual air intake shutdown, drip pan, wheel kit with 12" pneumatic tires, custom epoxy paint

SUMMARY: This pump set features the Kubota OC60, rated the No. 1 air/oil cooled diesel engine in the industry. The Kubota engine and AMT pump are matched to provide high flow and solids handling capability. The pump set and heavy duty skid design meets oilfield industry standards. The pump end is not designed to handle drilling fluids.

(SpecDPH2X2TAMT)