



KUBOTA / AMT 6X6 DIESEL TRASH PUMP OFFSHORE READY

SPECIFICATIONS:

MODEL: DPS6X6AMT

ENGINE: Kubota D1105 liquid cooled 3 cylinder diesel engine rated 26 hp @ 3000 rpm w/ mounted radiator, coolant recovery tank, air cleaner, manual air intake shutdown, muffler, spark arrestor, primary fuel filter, secondary fuel filter, electric fuel pump, 12 volt electric start w/ battery, box and cables, (air starter optional)

ENGINE CONTROLS: F.W. Murphy engine controls in weatherproof enclosure, hi temp, low oil shutdown, analog gauges, fuel stop solenoid, key switch, magnetic switch, alternator light, shielded wiring harness, (hour meter optional)

PUMP: AMT 6X6 npt trash pump rated up to 975 gpm, cast aluminum casing and adaptor, cast iron wear plate and volute, stainless steel impeller, solids handling to 3" diameter, silicone carbide mechanical seal, buna o-rings and check valve, suction strainer

SKID: Structural steel all welded galvanized roll frame w/ beveled drip pan, bottom drain, 4 Corner lift eyes, 12 gallon aluminum fuel tank CG approved, fuel gauge

DIMENSIONS: L 58" x W 31" x H 60" / 1600 lbs. dry

OPTIONS: Yard site trailer, DOT certified highway trailer, forklift pockets (roll frame unit), aluminum enclosure, in base 40 gallon fuel tank

SUMMARY: The Kubota engine and AMT pump are matched to provide high flow and solids handling capability. This pump set is designed for the rental industry to meet heavy duty industrial commercial pumping applications. High quality accessory components are used so this pump can be used in hazardous locations.

(SpecDPS6X6AMT)