



Phone 800-925-4966

Fax 504-393-1627

OFFSHORE READY DIESEL COMPRESSOR PACKAGE 7 ACFM @ 150 PSI

SPECIFICATIONS:

MODEL: DQC310SM30

ENGINE: Kubota OC60 air/oil cooled diesel engine rated 6hp @ 3600 rpm, 12 volt electric start, recoil start back up, mounted key switch w/wiring harness, manual air intake shutdown (poly), spark arrestor, fuel tank

COMPRESSOR: Quincy 310 air compressor rated 7 ACFM @ 150 PSI, 2 stage, pressure lubricated, spin on oil filter, dry type air filter, 2 groove power ban belt drive, unloader valve, load genie, pressure gauge

SKID: All welded galvanized roll frame, 2"x8"x3/16" box tubing, 2"x2"x3/16" tubing roll frame, vibration plate, stableflex isolators, beveled drip pan, bottom drain, 4 corner lift pad eyes (BHP Compliant), structural expanded metal belt guard, 30 gallon ASME approve volume tank, 12 volt battery w/box and cables, SS hardware, 4"x10" forklift pockets

WEIGHT / DIMENSIONS: L 53" x W 35" x H 62", 900 lbs.

WARRANTY: 2 year engine warranty major components, 1 year all other engine components, 1 year compressor, 90 day all accessories

SUMMARY: This engine/compressor package is offshore ready. It is designed and fabricated in form and function for various applications including cold starting, operation of air tools, supplying rig air, and any other application where portable compressed air is needed. The unit is assembled to meet the harsh offshore environment. The skid design ensures protection to all components and allows for safe transportation.

SpecDQC310SM30