



**OFFSHORE READY
BHP / SHELL COMPLIANT
DIESEL COMPRESSOR PACKAGE
18 ACFM @ 175 PSI**

SPECIFICATIONS:

MODEL: DQC325SM60

ENGINE: Kubota OC95 (tier 3 certified) air/oil cooled diesel engine rated 9.5hp @ 3600 rpm, 12 volt electric start, recoil start back up, mounted key switch, wiring harness, manual air intake shutdown (poly), spark arrestor, fuel tank

COMPRESSOR: Quincy 325 air compressor rated 18 ACFM @ 175 PSI, 2 stage pressure lubricated, spin on oil filter, dry type air filter, 2 groove power ban belt drive, unloader valve, load genie, pressure gauge

SKID: All welded galvanized roll frame (BHP / SHELL COMPLIANT), roll frame, 2" x 8" x 3/16" box tubing base, 2" x 2" x 3/16" tubing roll frame, 572 (4 corner) pad eyes, 11/16" shackle pin hole, 4" x 10" x 3/16" forklift pockets, 5/8" vibration plate, stableflex isolators, beveled drip pan, bottom drain, structural steel expanded metal belt guard, 60 gallon ASME certified volume tank, 1" discharge ball valve, 12 volt battery with box and cables, SS hardware

WEIGHT / DIMENSIONS: L 65" x W 38" x H 66" , 1200 lbs.

WARRANTY: 2 year engine major components, 1 year compressor, 90 days all accessories

SUMMARY: This engine/compressor package is offshore ready and BHP / SHELL Compliant. It is designed in form and function to meet various applications including cold starting engines, operation of air tools, supplying rig air and any other application where portable compressed air is needed. The unit is assembled to meet the harsh offshore environment. The skid design ensures protection to all components and allows for safe transportation.

SpecDQC325SM60