



Phone 800-925-4966

Fax 504-393-1627

OFFSHORE READY

DIESEL COMPRESSOR PACKAGE

95 ACFM @ 200 PSI

MODEL: DQC5120SM30

SPECIFICATIONS:

ENGINE: Kubota D1703M liquid cooled diesel engine, tier 3 certified, rated 36 HP @ 2800 rpm, assembled with mounted radiator, coolant recovery tank, air cleaner, muffler, spark arrestor, fuel filter, air start, idler pulley assy, EZ oil drain valve, stub shaft, epoxy coated

COMPRESSOR: Quincy 5120 rated 95 ACFM @ 200 PSI @ 940 RPM, 2 stage, pressure lubricated, spin on oil filter, dry air cleaner, 3 groove power ban, unloader, pressure gauge, air quality tested, epoxy coated

SKID: All welded structural steel galvanized skid, box tubing roll frame, vibration plate, stableflex vibration isolators, 4 corner lift, drip pan, 18 gallon USCG approved fuel tank, 30 gallon ASME air volume tank, aluminum belt guard, 4 diver manifold, stainless steel hardware

WEIGHT / DIMENSIONS: L 80" x W 46" x H 50" / 2200 lbs.

WARRANTY: 2 year engine, 1 year compressor, 90 days all accessories

SUMMARY: This engine/compressor package is dive ready and will meet SHELL lifting standards and all USCG requirements. It is designed in form and function to operate in the harsh offshore saltwater environment. Other applications include cold starting, operating air tools, supplying rig air, and any other application where portable compressed air is needed.

SpecDQC5120SM30