



Phone 800-925-4966

Fax 504-393-1627

**OFFSHORE READY
DIESEL PRESSURE WASHER
6 GPM @ 4000 PSI**

ENGINE: Kubota Diesel Engine Liquid Cooled (25 hp @ 3000 rpm)

PUMP: Triplex Pump, Direct Drive w/Gear Reduction (6 gpm @ 4000 psi)

SKID: Structural Steel all Welded and Galvanized w/Drip Pan, Forklift Pockets, 4 Corner Lift Eyes, Engine Vibration Plate w/Vibration Isolators, Wand Rack, Hose Rack, 12 Gallon Aluminum Fuel Tank, (CG Approved), Electric Fuel Pump

CONTROLS: Weather Proof Instrument Box, Hi Temp and Low Oil Shutdown, Key Switch, Shielded Wiring Harness, (Hour Meter Optional)

ACCESSORIES: Trap Pressure Unloader, Heavy Duty Trigger Gun w/Trigger Lock, 36" Lance Assy, 50ft HP Discharge Hose w/QC's, 5 Spray Nozzles, (Turbo Nozzle Optional), 10 Micron Inlet Water Filter, Crow Foot Connection

SAFETY FEATURES: Spark Arrestor, Manual Air Intake Shutdown, Thermo Pump Protector, Primary and Secondary Fuel Filters

DIMENSIONS / WEIGHT: L 53" x W 33" x H 46", 950 lbs. dry

WARRANTY: 2 Year Engine, 1 Year Pump, 90 Days Accessories

SUMMARY: This unit features a direct drive pump w/gear reduction. It is designed in form and function to meet heavy duty industrial commercial, marine, chemical and oil field cleaning applications. The skid design insures protection to all components and allow for safe loading/unloading for transportation. The unit is supplied with all necessary safety equipment for Offshore Applications.

(SpecKD4006GOE)