



Phone 800-925-4966

Fax 504-393-1627

OFFSHORE READY DIESEL PRESSURE WASHER 5 GPM @ 5000 PSI

SPECIFICATIONS

MODEL: KD5005GOE

ENGINE: Kubota Diesel Engine Liquid Cooled (22.5 hp @ 3000 rpm)

PUMP: Triplex Pump, Direct Drive w/Gear Reduction (5 gpm @ 5000 psi)

SKID: Structural Steel all Welded and Galvanized w/Drip Pan, Forklift Pockets, 4 Corner Cold Cut Pad Eyes, Engine Vibration Plate w/Vibration Isolators, Wand Rack, Hose Rack, 12 Gallon Aluminum Fuel Tank (Coast Guard Approved), Electric Fuel Pump

CONTROLS: Weather Proof Instrument Box, w/High Temp/Low Oil Shutdown Switches, Key Switch, Shielded Wiring Harness (Hour Meter Optional)

ACCESSORIES: Trap Pressure Unloader, Heavy Duty Trigger Gun w/Trigger Lock, 36" Lance Assy, 50ft HP Discharge Hose w/QC's, 5 Spray Nozzles, (Turbo Nozzle Optional), 10 Micron Inlet Water Filter, Crow Foot Water Connection

SAFETY FEATURES: Spark Arrestor, Manual Air Intake Shutdown, Thermo Pump Protector, High Pressure Relief Valve, Primary and Secondary Fuel Filters

DIMENSIONS/WEIGHT: L 53" x W 33" x H 46", 950 lbs.

WARRANTY: 2 Year Engine, 1 Year Pump, 1 Year Accessories

SUMMARY: This unit features a direct drive pump w/gear reduction. It is designed in form and function to meet heavy duty industrial commercial, marine, chemical and oilfield cleaning applications. The skid design insures protection to all components and allows for safe loading/unloading for transportation. The unit is supplied with all necessary safety equipment for Offshore Applications.

(SpecKD5005GOE)