



**OFFSHORE READY  
DIESEL HOT/COLD WATER PRESSURE WASHER  
MODEL: KD5006DH12V  
LIST OF SPECIFICATIONS**

**RATED:** 6 GPM @ 5000 PSI @ 160 Degrees F

**SKID:** Structural steel all welded, galvanized with beveled drip pan, bottom drain, 2"x8"x3/16" box tubing base, 2"x2"x3/16" tubing for roll frame, 4 corner lift pad eyes (BHP Compliant), 4"x10" forklift pockets

**ENGINE:** Kubota diesel engine rated 24 hp @ 3000 rpm, engine mounted radiator, air cleaner with manual air intake shutdown, muffler with spark arrestor, fuel filter, mechanical and electrical fuel pumps.

**PUMP:** Udor triplex pump, direct gear drive, rated 6 gpm @ 5000 psi, oil bath crankcase, nickel plated manifold, ceramic pistons, stainless steel valves.

**BRUNER:** Stainless steel combustion chamber, diesel fired with schedule 80 coils, lay down configuration, 12-volt burner system (no generator).

**ACCESSORIES:** Coast guard approved 11 gallon fuel tank with fuel gauge, dual racor fuel/water separators, 10 micron inlet water filter, weather proof junction box with terminal strip, weather proof instrument box with engine controls, shielded wiring harness, chemical injector assy, 4 point vibration system with fail safe isolators, trap pressure unloader mounted on pressure block, 12 volt battery with box, 36" lance assy, trigger gun, 5 spray nozzles, 50ft discharge hose assy with QC's.

**SAFTEY EQUIPMENT:** Flow switch burner control, rupture disc, high pressure relief valve, manual air intake shutdown (poly), spark arrestor, safety lock on trigger gun, engine controls hi/temp and low oil shutdown, fail safe isolators

**OPTIONAL EQUIPMENT:** Sandblast attachment, turbo nozzle, two gun operation, surface cleaner, telescoping lance assy, pipe cleaning nozzle w/foot valve control

(KD5006GH12V)