



Phone 800-925-4966

Fax 504-393-1627

OFFSHORE READY DIESEL PRESSURE WASHER 5 GPM @ 6000 PSI

ENGINE: Kubota 3 Cylinder Diesel Engine Liquid Cooled (26 hp @ 3000 rpm)

PUMP: Triplex Pump, Direct Drive w/Gear Reduction (5 GPM @ 6000 PSI)

SKID: Structural Steel all Welded and Galvanized w/Drip Pan, Forklift Pockets, 4 Corner Lift Eyes, Engine Vibration Plate w/Vibration Isolators, Wand Rack, Hose Rack, 12 Gallon Aluminum Fuel Tank w/Gauge (Coast Guard Approved), Electric Fuel Pump

CONTROLS: Weather Proof Instrument Box w/High Temp/Low Oil Shutdown Switch
Gauges, Key Switch, Shielded Wiring Harness, Weather Proof Terminal Strip (Hour Meter Optional)

ACCESSORIES: Trap Pressure Unloader, Heavy Duty Shutoff Gun w/Trigger Lock, 36" Lance Assy, 50ft x 3/8 Discharge Hose Assy w/QC's, 5 Spray Nozzles, Turbo Nozzle, 10 Micron Inlet Water Filter, Crow Foot Connector

SAFETY FEATURES: Spark Arrestor, Manual Air Intake Shutdown, Thermo Pump Guard, High Pressure Relief Valve, Primary and Secondary Fuel Filters

DIMENSIONS: L 53in. x W 33in. x H 46in., 950 lbs. (dry)

WARRANTY: 3 years engine, 1 year pump, 1 year accessories

SUMMARY: This unit features a direct drive triplex pump w/gear reduction. It is designed in form and function to meet heavy duty industrial commercial, marine and chemical plant cleaning applications. The skid design insures protection to all components and makes the unit easy to load/unload for transportation. The unit is supplied with all necessary safety equipment for **Offshore Applications. The unit is suitable for Environmental Contractors, Shipyards, Oil and Gas Service Companies and Rental Companies.**

(SpecKD6005GOE)