



Phone 800-925-4966

Fax 504-393-1627

**KG40KWRCE
KUBOTA DIESEL GENERATOR
RADIATOR COOLED
RATED 40 KW @ 1800 RPM**

SPECIFICATIONS:

ENGINE: Kubota 4 cylinder liquid cooled diesel engine rated 55 hp @ 1800 rpm, engine mounted radiator, coolant recovery tank, air cleaner, muffler, fuel filter, F.W. Murphy deluxe engine controls and gauge panel with hi temp and low oil shutdown, 12 volt electric start.

GENERATOR: Marathon 40KW dedicated single or three phase, 1800 rpm, AC brushless, epoxy coated, automatic voltage regulator, self excited, dynamically balanced rotor, fan cooled.

Skid: Structural steel skid, all welded and painted, stableflex vibration mounts (neoprene, marine duty), 12 Volt mounted battery with box and cables.

ENCLOSURE: Aluminum enclosure with side inspection doors, stainless steel hinges, hardware and latches, louvered rear panel, expanded metal front cap

WARRANTY: 2 year engine major components, 1 year generator

SUMMARY: This engine generator set is designed for continuous applications. It is assembled with high quality accessories and provides the reliability needed for standby generator applications.

(SpecKG40KWRCE)