



Phone 800-925-4966

Fax 504-393-1627

**KG5KWRCE
KUBOTA DIESEL GENERATOR
RADIATOR COOLED
RATED 5KW @ 1800 RPM**

SPECIFICATIONS:

ENGINE: Kubota 3 cylinder liquid cooled diesel engine rated 7.9 hp @ 1800 rpm, engine mounted radiator, coolant recovery tank, air cleaner, muffler, fuel filter, F.W. Murphy gauge panel, hi temp and low oil shutdown, 12 volt electric start

GENERATOR: Marathon/Newage 5KW dedicated single phase (3 phase optional), 1800 rpm, 120/240V, AC brushless, epoxy coated, automatic voltage regulator, self excited, dynamically balanced rotor, fan cooled

SKID: Structural steel skid all welded and painted, mounted 12 volt battery with box and cables, stableflex neoprene vibration isolators

ENCLOSURE: Aluminum enclosure with side inspection doors, stainless steel hinges, hardware, and latches, louvered rear panel, expanded metal front cap

WARRANTY: 2 year engine major components, 1 year generator

SUMMARY: This engine generator set is designed for continuous duty applications. It is assembled with high quality accessories and provides the reliability needed for standby generator applications.

(SpecKG5KWKCE)