



**DIESEL HOT/COLD  
PRESSURE WASHER  
4 GPM @ 3500 PSI @ 190F**

**MODEL:** KS3504GH12V

**ENGINE:** Kubota Diesel Liquid Cooled (16 hp) mounted Radiator, Air cleaner, Muffler, Fuel Filter, Fuel Stop Solenoid

**PUMP:** Triplex Pump (4 GPM @ 3500 PSI) Gear Reduction, Direct Drive, Oil Filled Crankcase, Bronze Connecting Rods, Extra Heavy Duty Roller Bearings

**SKID:** Structural Steel all Welded, 4 Corner Lift Eyes, 12 Gallon Aluminum Fuel Tank w/Gauge (Coast Guard Approved)

**CONTROLS:** Weather Proof Instrument Box w/High Temp/Low Oil Shutdown Switch Gauges, Shielded Wiring Harness, Weather Proof Terminal Strip, 12 Volt Battery w/Box, Electric Fuel Pump

**BURNER:** Stainless Steel Combustion Chamber, 12 Volt Burner, Fuel Water Separator

**ACCESSORIES:** Trap Pressure Unloader, Heavy Duty Shutoff Gun w/Trigger Lock, 36" Insulated Lance Assy, 50ft x 3/8 Discharge Hose Assy w/QC's, 5 spray nozzles, Turbo Nozzle, Inlet Water Filter w/Crow Foot Connector, Chemical Injector Assy

**SAFTEY FEATURES:** Thermo Pump Guard, High Pressure Relief Valve, High Heat Switch, Primary and Secondary Fuel Filters

**DIMENSIONS:** L 46in. x W 44in. x H 44in., 900 lbs. (dry)

**WARRANTY:** 2 years engine, 1 year pump, 1 year accessories

**SUMMARY:** The unit features **belt free operation**. The pump is direct drive from flywheel end of engine. The burner motor is powered by the 12 volt battery and charged by the engines high amp alternator. The skid design provides protection to all components and makes the unit easy to load/unload for transportation.

(SpecKS3504GH12V)