



Phone 800-925-4966

Fax 504-393-1627

**DIESEL HOT/COLD
PRESSURE WASHER
4 GPM @ 4000 PSI @ 170F**

MODEL: KS4004DH12V

ENGINE: Kubota Diesel Liquid Cooled (16 hp) mounted Radiator, Air cleaner, Muffler, Fuel Filter, Fuel Stop Solenoid

PUMP: Triplex Pump (4 GPM @ 4000 PSI) Direct Drive, Oil Filled Crankcase, Bronze Connecting Rods, Extra Heavy Duty Roller Bearings

SKID: Structural Steel all Welded, Forklift Pockets, Center point Lift, 12 Gallon Aluminum Fuel Tank w/Gauge (Coast Guard Approved)

CONTROLS: Weather Proof Instrument Box w/High Temp/Low Oil Shutdown Switch Gauges, Shielded Wiring Harness, Weather Proof Terminal Strip, 12 Volt Battery w/Box, Electric Fuel Pump

BURNER: Stainless Steel Combustion Chamber, 12 Volt Burner, Fuel Water Separator

ACCESSORIES: Trap Pressure Unloader, Heavy Duty Shutoff Gun w/Trigger Lock, 36" Insulated Lance Assy, 50ft x 3/8 Discharge Hose Assy w/QC's, 5 spray nozzles, Turbo Nozzle, Inlet Water Filter w/Crow Foot Connector, Chemical Injector Assy

SAFTEY FEATURES: Thermo Pump Guard, High Pressure Relief Valve, High Heat Switch, Primary and Secondary Fuel Filters

DIMENSIONS: L 46in. x W 44in. x H 44in., 900 lbs. (dry)

WARRANTY: 2 years engine, 1 year pump, 1 year accessories

SUMMARY: The unit features **belt free operation**. The pump is direct drive from flywheel end of engine. The burner motor is powered by the 12 volt battery that is charged by the engines high amp alternator. The skid design provides protection to all components and makes the unit easy to load/unload for transportation. This equipment is **Rental Quality, suitable for Environmental Contractors, Oil and Gas Service Companies and Petrochemical Plants.**

(SpecKS4004DH12V)