



**ONSHORE READY
6 GPM 5000 PSI
HOT/COLD DIESEL PRESSURE WASHER**

Engine: Kubota diesel engine rated 24 hp @ 3000 rpm, engine mounted radiator, air cleaner with manual air intake shutdown, muffler with spark arrestor, fuel filter, mechanical and electrical fuel pumps.

Pump: Triplex Pump, Direct Drive with Gear Reduction (6 gpm @ 5000 psi)

Skid: Structural Steel Type, Galvanized, Center point lift, Aluminum Fuel Tank (coast guard approved), Replaceable 10 Micron Inlet Filter, 4 Point Vibration Isolation System

Burner: 12 volt, Diesel fired, Stainless Steel Combustion Chamber, Temperatures up to 190 degrees Fahrenheit

Controls: Weather Proof Instrument Box with High Temperature/Low Oil Shutdown, Switch Gauges, Shielded Wiring Harnesses with Weather Proof Terminal Strip

Safety Features: Rupture Disc, Flow and Pressure Switch, Thermo Pump Protector, High Pressure Relief Valve

Dimensions/Weight: L 55" x W 49" x H46", 1800 lbs. (dry)

Warranty: 2 year engine, 1 year pump, 1 year accessories

Summary Features: The unit features belt free operation to reduce overall vibration. It is designed in form and function to meet heavy duty, industrial commercial, marine and chemical plant cleaning applications. The skid design insures protection to all components and makes the unit easy to load/unload for transportation. This unit provides the safest possible operation. The redundant filter system for both fuel and water gives the user reliable operation in remote locations.

(SpecKS5006GH12V)