



**BHP COMPLIANT
OFFSHORE READY
DIESEL LIGHT TOWER / GENERATOR
CLASS I DIV 2
10KW @ 1800 RPM**

LIST OF SPECIFICATIONS:

MODEL: OSLT10KWBHP

ENGINE: Kubota diesel engine, **D1105EBG, 3 cylinder liquid cooled (18 hp @ 1800 rpm, tier 3 certified)**, mounted radiator, coolant recovery tank, air cleaner, Chalwyn automatic and manual air intake shutdown, muffler, Super Trapp spark arrestor, 12 volt electric start, electric fuel pump, Racor primary fuel filter, secondary spin on fuel filter, F.W. Murphy engine controls, Hi temp and Low oil shutdown, hour meter, EZ oil drain valve

GENERATOR: Newage **10KW**, dedicated single phase, 4 pole, single bearing, 1800 rpm, 120/240V, AC brushless, epoxy coated, automatic voltage regulator, self excited, dynamically balanced rotor, fan cooled

LIGHTING: 4 – General Electric Metal halide (Class 1 Div 2) 400 watt lights with fixtures, retractable SO cord, circuit breaker protection, weatherproof enclosure, expanded aluminum lens covers

RECEPTICLES: 3 – 110V, 1 – 240V Killark explosion proof receptacles (Class 1 & 2), circuit breaker protected, 2 tumbler switch for on/off light control, ground fault protection for lights and receptacles, 20 amp circuit breakers

SKID: Structural steel all seal welded skid with 4"x8"x3/16" box tubing base, 2"x2"x3/16" tubing roll frame, 4 corner lift pad eyes with 572 plate strength, 3/4" width, 7/8" shackle pin hole drilled, pull tested, stress tested and certified with documents, 4"x10"x3/16" box tubing forklift pockets, 2" above bottom of skid, top fiberglass grating, beveled drip pan with bottom drain, aluminum engine enclosure with side inspection door, stableflex neoprene vibration isolators, 30 gallon aluminum CG approved fuel tank with fuel gauge, aluminum storage box 24"x19"x16", stainless steel hardware

BOOM: (PATENT PENDING) Structural steel all seal welded and galvanized 16ft telescoping boom, single stage with Teflon guides, rotating mast, 360 degree lighting capability, hand winch with locking break, galvanized 1/4" cable, stainless steel pulleys, locking pin when boom is extended, expanded metal winch guard

DIMENSIONS / WEIGHT: L 64" x W 62" x H 86" / 2700 lbs. dry

WARRANTY: 2 year engine warranty major components or 2000 hrs, 1 year all other engine components, 1 year generator, 90 days accessories

DOCUMENTATION: Engineered BHP compliant skid with stress test, pull test and certifications

Call for pricing and delivery.

(SpecOSLT10KWBHP)

(2)